

TECHNICAL SPECIFICATION

RESPIRATORY PROTECTION



Flexinet® Mask FFP3 Valved (832)

Box of 5 / Code: BER130-001-M00



DESCRIPTION

The Flexinet™ disposable mask has an ergonomic 3D design to fit most face shapes, with extremely low breathing resistance and mesh outer shell to help the mask retain its shape.

- High efficiency (99% minimum) filtering.

OPTIONS

Box of 5 (BER130-001-M00)

DOWNLOADS


-  [Image Pack \(ZIP\)](#)
-  [Declaration of Conformity \(PDF\)](#)



JSP Limited. Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.
Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com
Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com.
Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.
Page 1 of 3 / Issued 16 Nov 2020 / Copyright 2018 - 2020. JSP Limited. All Rights Reserved.



FEATURES



Comfort

A 360° comfort foam area around the inside of the mask provides a perfect fit.



Protective Grill

Flexible cover to protect and retain the shape of the mask and protect the wearer against possible damage to the filter.

Advanced Valve

Advanced design valve allows for lower breathing resistance.

COMPATIBLE PRODUCTS

EVO® Gas Goggle
EVO® Goggle Double Lens
EVO® Goggle Single Lens
Stealth™ 16G
Stealth™ 7000
Stealth™ 8000
Stealth™ 9000
Stealth™ Coverlite™ Overspec
Thermex™ Double Lens Goggle

ACCESSORIES

Portacount/AccuFIT Quantitative/Qualitative Face Fit Testing Kit & Spares

SAFETY STANDARDS

EN 149

SPECIFICATIONS

Classification

FFP3 (Filtering Facepiece Particulate)



Filter Type

P (Protects Against Solid and Liquid Aerosol)

Usage

NR (Non-Reusable)



(D) Resistance to dust clogging

Yes – D marking = passes optional clogging test



Activated Carbon Layer

No

Minimum Filtration Efficiency

99% For FFP3 Rated

Maximum Total Inward Leakage (TIL)

2%

Nominal Protection Factor

50

UK Assigned Protection Factor

20

Mask Design

Mesh Outer Shell



Exhalation Valve

Advanced Valve



4 Point Harness adjustment system

Yes



Nose Bridge

Moulded

Latex free

No

Metal Free

Yes

Mask Material

Polypropylene

Filter Shelf Life

5 Years



BSI Kitemark

Yes



Product Weight

26g

APPLICATIONS

Agricultural

- Arborist
- Chemical Spraying
- Distribution
- Farming
- Grain Stores
- Landscaping

Construction and Infrastructure

Facilities Management

- Elevator Maintenance & SVS

Food and Drink Manufacturing

Law Enforcement



- UN Forces

Manufacturing

- Paper
- Wood and Timber

Utilities Contractors

- Electrical

RANGE

